



ZUMTOBEL

**ZOOM! 10 Day
Program**

Manufactured – ships in 10 days.

ZOOM! 10 Day Terms & Conditions

ZOOM! 10 Day products ship within (10) business days.

To find a Zumtobel agent in your area please visit zumtobel.us or call us at 800.448.4131.

Please go to zumtobel.us/products for more information on the ZOOM!10 Day program.



BASYS™ LED II

Improved Efficacy



LED **NEW** Up to 30% higher efficacy over BASYS LED!

BASYS™ LED II

Available in Round or Square with semi-specular reflectors and natural or white-painted* flange

Designed for maximum visual comfort, performance and efficacy

Perfect for applications with restricted plenum space

No visible LED "dots"

2700K, 3000K, and 3500K LED modules available*

Emergency back-up options available*

* See program guide for details on availability

	Size	Wattage/Output	Type	Driver
	4"	14W, 1000 lm	Downlight	120/277V 0-10V Dimming
	4"	14W, 700 lm	Wallwasher	120/277V 0-10V Dimming
	4"	22W, 1400 lm	Downlight	120/277V 0-10V Dimming
	4"	22W, 980 lm	Wallwasher	120/277V 0-10V Dimming
	6"	18W, 1400 lm	Downlight	120/277V 0-10V Dimming
	6"	18W, 1000 lm	Wallwasher	120/277V 0-10V Dimming
	6"	37W, 2800 lm	Downlight	120/277V 0-10V Dimming

For more detailed technical product information, go to zumtobel.us/products and select 10 Day Shipping under product filter.

SLOTLIGHT LED II

Linear Perfection



LED

NEW

**Up to 25% higher efficacy
over SLOTLIGHT LED!**

SLOTLIGHT LED II available on ZOOM! 10 Day program starting December 1, 2014

SLOTLIGHT LED II

Uniform illumination from end to end

High efficiency allows for designs with fewer fixtures, helping meet strict energy codes

Ideal for applications in restricted space

2.5", 4", or 6" aperture

Lengths are nominal

Opal Flush Lens

Emergency back-up options available*

** Lay-In fixtures compatible with Armstrong TechZone and USG Logix ceilings

* See program guide for details on availability

Length	Output	Mounting**	Electrical	Type
4'	450 lm/ft 750 lm/ft	Sheetrock Flangeless Lay-In 15/16" Tee Lay-In 9/16" Slot Grid or Tegular	120/277V 0-10V Dimming	Individual
8'	450 lm/ft 750 lm/ft	Sheetrock Flangeless Lay-In 15/16" Tee Lay-In 9/16" Slot Grid or Tegular	120/277V 0-10V Dimming	Individual
12'	450 lm/ft 750 lm/ft	Sheetrock Flangeless Lay-In 15/16" Tee Lay-In 9/16" Slot Grid or Tegular	120/277V 0-10V Dimming	Individual

For more detailed technical product information, go to zumtobel.us/products and select 10 Day Shipping under product filter.

ML4™ Opal

High Performance
Mellow Light



ML4™ Opal

All options come with Opal Lens and "U" Mounting

Ideal for offices, retail, healthcare, and educational facilities

Perfect for visual comfort

Emergency back-up options available*

* See program guide for details on availability

Size	Lamping	Mounting	Electrical
2' x 2'	(2) 14W T5	9/16" Slot-In, Grid 9/16" Lay-In, Tegular 15/16" Lay-In, Flush	120/277V EM Lutron EcoSystem H-Series Dimming
2' x 2'	(2) 24W T5 HO	9/16" Slot-In, Grid 9/16" Lay-In, Tegular 15/16" Lay-In, Flush	120/277V EM Lutron EcoSystem H-Series Dimming
1' x 4'	(1) 28W T5 (2) 28W T5 (2) 32W T8 (1) 54W T5 HO	9/16" Slot-In, Grid 9/16" Lay-In, Tegular 15/16" Lay-In, Flush	120/277V EM Lutron EcoSystem H-Series Dimming
2' x 4'	(2) 28W T5 (2) 32W T8 (2) 54W T5 HO	9/16" Slot-In, Grid 9/16" Lay-In, Tegular 15/16" Lay-In, Flush	120/277V EM Lutron EcoSystem H-Series Dimming

ZX52

Effective
Distribution



ZX52

All options come with Aisle Optic with White Cross-Blades, White Housing and Universal 120/277V Ballast

Starters and Individual fixtures come with 70" feed cord

Order Individual fixtures, or order Starters, Mids, Ends, and Suspensions for Continuous Runs

Power Feed Suspensions and Non-Power Feed Suspensions available

Size	Lamping	Electrical	Type
4'	(1) 54W T5 HO	120/277V	Start Mid End Individual
8'	(2) 54W T5 HO	120/277V	Start Mid End Individual
12'	(3) 54W T5 HO	120/277V	Start Mid End Individual

KAVEROS™

A Clean Beam with a Stylish Look



KAVEROS™

Painted white texture

GES 1 circuit track adapter included with fixture for use with 1 circuit 120V Global Track

Additional optic accessories available (snoot, spread lens, hexcell louver, Solite lens)

Can hold up to two optical accessories at a time

Size	Lamping	Type	Electrical
Small 2"	12W	Flood	UNV, GES
	2700K 3000K	Narrow Flood Spot	
Medium 3"	18W	Flood	UNV, GES
	3000K	Narrow Flood Spot	
Large 4"	18W	Flood	UNV, GES
	3000K	Narrow Flood Spot	

GLOBAL TRACK

White finish

Multiple accessories and mounting options available, including 24" and 48" pendant stem and canopy kits, couplers and end feeds

Track is field cuttable

Length	Type	Voltage
4'	GES 1 Circuit	120V
8'	GES 1 Circuit	120V

SPEC-5

Comfortable
Efficiency



SPEC-5

All options come with: Matte Clear Trim and White Painted Flange

Offers excellent brightness control in a 6" aperture

Reflector is one piece spun aluminum with ½" flat flange with low iridescence, specular clad finish

Emergency back-up options available*

* See program guide for details on availability

Size	Lamping	Type	Electrical
6"	26W/32W/42W CFL	Downlight	120/277V
6"	26W/32W/42W CFL	Wallwasher	120/277V
6"	26W/32W/42W CFL	Downlight	347V
6"	26W/32W/42W CFL	Wallwasher	347V
6"	26W/32W/42W CFL	Downlight	Dimming
6"	26W/32W/42W CFL	Wallwasher	Dimming



ZUMTOBEL

a member of
zumtobel group

ZOOM! 10 Day Program

Manufactured – ships in 10 days.



Zumtobel Lighting, Inc.
3300 Route 9W
Highland, NY 12528

Main: 845-691-6262
Toll Free: 800-448-4131
Email: zli.us@zumtobelgroup.com

www.zumtobel.us

D00353CA 10/14 © Zumtobel Lighting, Inc.
In a continuing effort to offer the best product possible we reserve the right to change, without notice, specifications or materials that in our opinion will not alter the function of the product. Technical data was correct at time of going to press.

