

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

Fixed general purpose luminaires

Name and address of the applicant

Zumtobel Lighting GmbH
Schweizer Str. 30,
6850 Dornbirn, Austria

Name and address of the manufacturer

Zumtobel Lighting GmbH
Schweizer Str. 30,
6850 Dornbirn, Austria

Name and address of the factory

Zumtobel Lighting GmbH
Schweizer Str. 30,
6850 Dornbirn, Austria

Note: When more than one factory, please report on page 2

☐ Additional Information on page 2

Ratings and principal characteristics

220-240 V; 0/50/60 Hz; C.I.I;
IP65 for series AMP R...,
IP20 for series AMP... TEC

Trademark / Brand (if any)

 **ZUMTOBEL**

Customer's Testing Facility (CTF) Stage used

CTF Stage 2

Model / Type Ref.

Series AMP... TEC,
Series AMP R...,
see page 2 and 3

Additional information (if necessary may also be reported on page 2)

Light source classified as RG1 according to IEC 62471:2006.
Also available as centrally supplied maintained emergency luminaire
(classification Z 1) according to IEC 60598-2-22:2014 + AMD1:2017
see test report TR-251-0118-03 (optional).☒ Additional Information on pages 2 to 3

A sample of the product was tested and found to be in conformity with

IEC 60598-1:2014 IEC 60598-2-1:1979
IEC 60598-1:2014/AMD1:2017 IEC 60598-2-1:1979/AMD1:1987

As shown in the Test Report Ref. No. which forms part of this Certificate

TR-251-0118-01

This CB Test Certificate is issued by the National Certification Body

Typecode:

AMP -

Through wiring

None

Quick connect

TEC..... Tecton connection

Emergency

None

Sensor

MWS Micro wave sensor

MWCF Micro wave sensor
corridor function

MWRF Micro wave sensor

Radio Frequency (Master)

RF Radio frequency (Slave)

None

Type of ballast

EVG not dimmable

LDO only DALI dimmable

IVG Industry

N4M Net for more

Light distribution

AB Asymetric Beam

MB Middle beam

NB Narrow beam

WB Wide beam

Material of housing

PC Polycarbonate

PM Polymethylmethacrylat

CH Chemo

Luminous colour

830, 840, 865

Lumen output

2900 - 10000

Application

BAS Polycarbonate

LT low temperature

None

Dimension


S Small

L Large

Luminaire series

Additional information (if necessary)

Date: 2020-11-26



Digitally signed by W. Martin
Email=w.martin@ove.at

Signature: Dipl.-Ing. W. Martin

Typecode:

AMP R. -

Closure

KST Plastic Clips

V2A Metall Clips

Type of ballast

LDO only DALI dimmable

Luminous colour

830, 840

Lumen output

3000 - 5600

Dimension


S Round S

L Round L

Luminaire series

Additional information (if necessary)

Date: 2020-11-26

Digitally signed by W. Martin
Email=w.martin@ove.at

Signature: Dipl.-Ing. W. Martin