

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

Luminaires with limited surface temperatures

Name and address of the applicant

Zumtobel Lighting GmbH
Schweizer Str. 30,
6850 Dornbirn, Austria

Name and address of the manufacturer

Zumtobel Lighting GmbH
Schweizer Str. 30,
6850 Dornbirn, Austria

Name and address of the factory

Zumtobel Lighting GmbH
Schweizer Str. 30,
6850 Dornbirn, Austria

Note: When more than one factory, please report on page 2

☒ Additional Information on page 2

Ratings and principal characteristics

220-240 V; 0/50/60 Hz; IP64; Cl.I; ▽-Marking

Trademark / Brand (if any)



ZUMTOBEL

Customer's Testing Facility (CTF) Stage used

CTF Stage 2

Model / Type Ref.

Series TECTON C ... IP64,
see page 3

Additional information (if necessary may also be reported on page 2)

Light source classified as risk group 1 (low risk).
Also available as centrally supplied maintained emergency luminaire (classification Z 1) according to IEC 60598-2-22:2021, see test report TR-251-0188-01.

See test report for information about National and/or Group

A sample of the product was tested and found to be in conformity with

IEC 60598-1:2020
IEC 60598-2-24:2013

As shown in the Test Report Ref. No. which forms part of this Certificate

TR-251-0188-02

This CB Test Certificate is issued by the National Certification Body



Ref. Certif. No.

AT 5326

Additional factory:

ZG Lighting SRB doo
Ulica Cumtobel br. 1,
18000 Nis, Serbia

Additional information (if necessary)

Digitally signed by T. Neumayer
Email=t.neumayer@ove.at

Date: 2025-10-10

Signature: Dipl.-Ing. T. Neumayer

Typecode:
TECTON C L.... .. IP64
IP Version

IP64

Colour of luminaire

None

WH White

SR Silver

BK..... Black

Type of ballast

LDE Dimmable

LDO Dimmable (DALI only)

EVG..... Not dimmable

IVG Industry LED driver

Type of optic/diffuser

None

WB..... Wide Beam

VWB Very Wide Beam

NB Narrow Beam

SB..... Shelf Beam

WSB Wide Shelf Beam

WW..... Wallwasher

Length of luminaire

1000, 1500, 1522, 2000

Luminous colour

830, 835, 840, 865

Lumen output

2500 - 17000

Luminaire version

C

Luminaire series
Accessories:

TEC C LED BUCKLE SR IP64, TEC C LED BUCKLE WH IP64, TEC C LED ENCAP noV WH IP64,
 TEC C LED ENDCAP noV SR IP64, TEC C LED ENDCAP V SR IP64, TEC C LED ENDCAP V WH IP64,
 TEC C REFL WW L1000 SR IP64, TEC C REFL WW L1000 WH IP64, TEC C REFL WW L1500 SR IP64,
 TEC C REFL WW L1500 WH IP64, TEC C REFL WW L2000 SR IP64, TEC C REFL WW L2000 WH IP64,
 TECTON T AK SEAL ENDCAP SR IP64, TECTON T AK SEAL ENDCAP WH IP64,
 TECTON T SEAL STICKER IP64, TECTON TE COVER STRIP SR, TECTON TE COVER STRIP WH,
 TECTON TE ENDCAP SR IP64, TECTON TE ENDCAP WH IP64

Additional information (if necessary)

T. Neumayer
 Digitally signed by T. Neumayer
 Email=t.neumayer@ove.at

Date: 2025-10-10

Signature: Dipl.-Ing. T. Neumayer