



Ref. Certif. No.

AT 5014

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

Fixed luminaires for ceiling mounting with electrical supply track systems

Name and address of the applicant

Zumtobel Lighting GmbH
Grevenmarschstr. 74-78,
32657 Lemgo, Germany

Name and address of the manufacturer

Zumtobel Lighting GmbH
Grevenmarschstr. 74-78,
32657 Lemgo, Germany

Name and address of the factory

Zumtobel Lighting GmbH
Grevenmarschstr. 74-78,
32657 Lemgo, Germany

Note: When more than one factory, please report on page 2

☐ Additional Information on page 2

Ratings and principal characteristics

AC 220-240 V, 50/60 Hz; Cl.I; IP20;
LED 11, 19, 26,5, 27, 29, 32, 34, 35, 41, 43, 47, 50, 62 W

Trademark / Brand (if any)



Customer's Testing Facility (CTF) Stage used

CTF Stage 2

Model / Type Ref.

Series V2 S ..., V2 M ..., V2 L ..., V2-P M ..., see page 2.

Additional information (if necessary may also be reported on page 2)

See test report for information about National and/or Group Differences.

☒ Additional Information on pages 2 to 3

A sample of the product was tested and found to be in conformity with

IEC 60598-1:2020
IEC 60598-2-1:2020

As shown in the Test Report Ref. No. which forms part of this Certificate

TR 22159-0017-01

This CB Test Certificate is issued by the National Certification Body



Österreichischer Verband für Elektrotechnik

OVE Certification

Kahlenberger Str. 2A, 1190 Wien, Austria

T. Neumayer

Digitally signed by T. Neumayer
Email=t.neumayer@ove.at



Date: 2023-11-03

Signature: Dipl.-Ing. T. Neumayer

Typecode:

V2

Colour decorative front ring

WH.....white

BK.....black

Colour of housing

WH.....white

BK.....black

Optics

SP.....Spot reflector

MSP.....Midum reflector

FL.....Flood reflector

WFL.....Wide Flood reflector

VFL.....Very Wide Flood reflector

VOPT.....reflector + vertical optic

Cable (only for pendant version)

CWH.....cable white

CBK.....cable black

Adaptor

3GU.....3phase adapter GLOBAL

3CDC.....L3+DALI adapter only ceiling mounting

3CUC.....3phase universal adapter only ceiling mount.

3CY.....3phase universal adapter with TrackBox DALI

3CV.....3phase universal adapter with TrackBox

Type of controlgear / dimmable

SWI.....switchable gear

LDO.....controlled gear, DALI

BC.....Bluetooth Casambi controlled gear

Colour temperature / Photometric code

830.....3000K, CRI > 80

840.....4000K, CRI > 80

927.....2700K, CRI > 90

930.....3000K, CRI > 90

935.....3500K, CRI > 90

940.....4000K, CRI > 90

927-965.....Tuneable White

+927.....2700K, CRI > 97

+930.....3000K, CRI > 97

+940.....4000K, CRI > 97

MEAT.....1900K, CRI > 90

FISH.....4000K, CRI > 97

BKY.....2500K, CRI > 97

DELIC.....2700K, CRI > 97

FRUIT.....3000K, CRI > 97

CHEES.....2500K, CRI > 97

FASH.....3000K, CRI > 90

WHEX.....3500K, CRI > 90

Nominal luminous flux
Size

S.....Small

M.....Medium

L.....Large

Mounting (only for pendant version)

-P.....pendant

none.....spot

Luminaire series

V2.....VIVO II

Additional information (if necessary)

T. Neumayer
Digitally signed by T. Neumayer
Email=t.neumayer@ove.at
Signature: Dipl.-Ing. T. Neumayer

Date: 2023-11-03

Typelist:

Type	Rated power [W]	Current setting [mA]	LED-module	Track adaptor
V2-P M xxxx-yzz SWI 3CUC kkk ...	27	700	CLU03J-1208C9	3CUC
V2 S 1200-927-65 BC 3CV ...	19	450/350	BXRV LES 9mm (36V)	3CV
V2 M 2500-927-65 LDO 3CY ...	35	900/800	BXRV LES 15mm	3CY
V2 M 2500-927-65 BC 3CV ...	35	900/800	BXRV LES 15mm	3CV
V2 L 2800-927-65 LDO 3CY SP ...	35	900/800	BXRV LES 15mm	3CY
V2 L 3800-927-65 LDO 3CY ...	50	1250/1050	BXRV LES 18mm	3CY
V2-P M 2500-927-65 LDO 3CY kkk ...	35	900/800	BXRV LES 15mm	3CY
V2-P M 2500-927-65 BC 3CV kkk ...	35	900/800	BXRV LES 15mm	3CV
V2 L xxxx-9zz LDO 3CY SP ...	47	1200	CLU03J-1208C9	3CY
V2 L 6000-9zz LDO 3CY ...	62	1600	CLU04J-1212C9	3CY
V2 S 1200-927-65 LDO 3CY ...	19	450/350	BXRV LES 9mm (36V)	3CY
V2 M xxxx-yzz LDO 3CDC ...	26,5	700	CLU03J-1208C9	3CDC
V2 M xxxx-FASH LDO 3CDC ...	26,5	700	SLM 1208 G7	3CDC
V2 M xxxx-WHEX LDO 3CDC ...	26,5	700	SLM 1208 G7	3CDC
V2 L xxxx-yzz LDO 3CDC ...	32	850	CLU04J-1212C9	3CDC
V2 M xxxx-bbbb LDO 3CDC ...	26,5	700	CLU03J-1208C9	3CDC
V2 L xxxx-zyy LDO 3CDC SP ...	34	850	CLU03J-1208C9	3CDC
V2 L xxxx-yzz LDO 3CDC ...	32	850	CLU04J-1212C9	3CDC
V2 M xxxx-yzz SWI 3CUC ...	27	700	CLU03J-1208C9	3CUC
V2 M xxxx-FASH SWI 3CUC ...	27	700	SLM 1208 G7	3CUC
V2 M xxxx-WHEX SWI 3CUC ...	27	700	SLM 1208 G7	3CUC
V2 M xxxx-bbbb SWI 3CUC ...	27	700	CLU03J-1208C9	3CUC
V2 S xxxx-yzz LDO 3CY ...	29	700	CLU02J-1204C9	3CY
V2 M xxxx-yzz LDO 3CY ...	43	1050	CLU03J-1208C9	3CY
V2 M xxxx-FASH LDO 3CY ...	43	1050	SLM 1208 G7	3CY
V2 M xxxx-WHEX LDO 3CY ...	43	1050	SLM 1208 G7	3CY
V2 M xxxx-bbbb LDO 3CY ...	43	1050	CLU03J-1208C9	3CY
V2 L xxxx-yzz LDO 3CY ...	32	850	CLU04J-1212C9	3CY
V2 L xxxx-yzz LDO 3CY SP ...	43	1050	CLU03J-1208C9	3CY
V2 L xxxx-yzz LDO 3CY ...	41	1050	CLU04J-1212C9	3CY
V2 S 700-927-65 BC 3CV ...	11	500/425	BXRV LES 9mm (18V)	3CV
V2 M xxxx-yzz SWI 3GU ...	27	700	CLU03J-1208C9	3GU
V2 M xxxx-FASH SWI 3GU ...	27	700	SLM 1208 G7	3GU
V2 M xxxx-WHEX SWI 3GU ...	27	700	SLM 1208 G7	3GU
V2 M xxxx-bbbb SWI 3GU ...	27	700	CLU03J-1208C9	3GU

V2 VIVO II

V2-P VIVO II Pendant version

S, M, L Size

xxxx Nominal luminous flux

yzz Photometric code (y= code for CRI, zz= code for CCT)

bbbb alternative codes for special use (DELIC, BKY, FRUIT, FISH, MEAT, CHEES)

kkk Cable type (for pendant version only)

Additional information (if necessary)

T. Neumayer
Digitally signed by T. Neumayer
Email=t.neumayer@ove.at

Date: 2023-11-03

Signature: Dipl.-Ing. T. Neumayer